



SM1727-37

1700 MHz to 2700 MHz

POWER AMPLIFIERS



Featured and Options

- Options:
 TTL on/off
 Fan
 Heatsink
 Features:

Environmental Ratings

	Min	Typ	Max	Unit
Storage Temperature	-40		85	°C
Operating Temperature	-20		85	°C
Automatic Shut Off Temp		90		°C
Operating Humidity		95%		
Operating Altitude		30000		Ft

Connectivity

RF Input Connector	SMA F
RF Output Connector	SMA F
Control/Monitoring Connector	Feedthrough Pins

Specifications

	Min	Typ	Max	Unit
RF Frequency	1700		2700	MHz
P1dB Power Output	37	38		dBm
Linear Gain		33 ±1		dB
Gain Flatness Over Band		±1		dB
Gain Change Over Temp		±1		dB
Third Order Intercept (OIP3)		50		
Input Return Loss			-16	dB

Operating Characteristics

	Min	Typ	Max	Unit
Supply Voltage	11	12	13	VDC
Operating Current Draw	1.9	2.1		A

Pin Table

Pin	Value	Description

Notes



Microwave RF Components | Hudson, NH | (603) 546-4100 | rf.mrcy.com
Specifications subject to change without notice

[Request a Quote](#) | [Ask an Engineer](#)  

